

<b>PRODUCT NAME:</b>	<b>Inferno-Lite® ICGCP1216WW90</b>	
<b>PRODUCT CODE:</b>	ICGCP1216WW90	
<b>PERFORMANCE TESTING:</b>	Fire Rating:	Tested in accordance with UL Standard Fire Tests of Door Assemblies UL 10C for a 90 minute fire resistant rating with hose stream. UL File # KCMZ.R13833
	Attack Resistance:	ASTM F-1915 Grade 3, 20 minute containment rated HP White Level II-TP-0500.02 WMFL Level III
<b>CONSTRUCTION:</b>	1/4" Wire Glass .050" Urethane 1/8" Polycarbonate .025" Urethane 1/4" polycarbonate .050" Urethane 1/4" Wire Glass	
<b>THICKNESS:</b>	1" Nominal	
<b>THICKNESS TOLERANCE:</b>	.980" / 1.104"	
<b>WEIGHT:</b>	9.5 Lbs. / Square Foot	
<b>MAXIMUM SIZE:</b>	330 square inches of clear opening Maximum Exposed Viewing Area- Any size up to 10" x 33"	
<b>APPLICABLE STANDARDS:</b>	ANSI Z97.1 CPSC 16 CFR 1201 (Category I and II) ASTM C 1036	ASTM C 1349 UL 9 UL 10C
<b>SINGLE RESPONSIBILITY:</b>	Global Security Glazing products are covered by our Single Responsibility® Program that ensures one firm has handled and is accountable for all phases of manufacturing.	
<b>INSTALLATION:</b>	All glazing to be installed with UL classified Metacaulk 950 or Blazeseal joint treatment as manufactured by Metalines, Inc. to maintain UL label requirements. For general glazing guidelines refer to the Glass Association of North America (GANA) Glazing Manual 2004 or latest edition. Contact Global Security Glazing for publication GSG-23-03 "Glazing Guidelines" for further information.  Note: ICGCP1216WW90 is manufactured with two plies of wire glass which are impossible to align perfectly. Visibility may be obscured to some degree. ICGCP1216WW90 is only available in clear glazing.	