

PRODUCT NAME:

NIJ Level IV - Secur-Tem + Poly®

PRODUCT CODE:

SPN420

PERFORMANCE TESTING:

Ballistic: National Institute of Justice- 0108.01- Level IV
 .30-06 Armor Piercing
 No Spall, No Penetration

CONSTRUCTION:

Product construction is proprietary. This product is glass-clad polycarbonate and contains an exposed polycarbonate surface with an abrasion resistant coating on the witness (safe) side.

THICKNESS:

2" Nominal (2.00")

THICKNESS TOLERANCE:

1.88" / 2.11"

WEIGHT:

24.38 Lbs. / Square Foot

SIZE:

60" x 96" Maximum
 12" x 12" Minimum

OPTIONS:

Tinted glass, translucent interlayers, transparent mirror, Low Iron glass

TECHNICAL DATA:

U-Value- .68
 Shading Co-efficient- .64
 Light Transmission- .60

APPLICABLE STANDARDS:

ANSI Z97.1
 CPSC 16 CFR 1201 (Category I and II)
 ASTM C 1036
 ASTM C 1349

SINGLE RESPONSIBILITY:

Global Security Glazing products are covered by our Single Responsibility® Program that ensures one firm has handled and is accountable for all phases of manufacturing.

INSTALLATION:

Glass must be installed in a Bullet Resistant frame system. Holes must be covered with a ballistic rated device. All glass should be installed in accordance with the guidelines set forth in the current edition of the Glass Association of North America (GANA) Glazing and Sealant Manuals. Glazing systems should incorporate a weep system to allow moisture and water to escape the glazing channel.

Recommended Clearance:

Face: 1/8" per side
 Edge: 3/8"
 Bite: 1"